



US007075892B2

(12) **United States Patent**
Grover et al.

(10) **Patent No.:** **US 7,075,892 B2**

(45) **Date of Patent:** **Jul. 11, 2006**

(54) **TOPOLOGICAL DESIGN OF SURVIVABLE MESH-BASED TRANSPORT NETWORKS**

2002/0071392 A1 6/2002 Grover et al. 370/241

OTHER PUBLICATIONS

(75) Inventors: **Wayne D. Grover**, Edmonton (CA);
John Doucette, Edmonton (CA)

A photocopy of Canadian Patent Application No. 2,161,847, filed Oct. 31, 1995 (published May 1, 1997), including drawings and filing certificate, 32 pages.

(73) Assignee: **Telecommunications Research Laboratories**, Edmonton (CA)

A photocopy of Canadian Patent Application No. 2,212,933, filed Aug. 13, 1997 (published Feb. 13, 1999), including drawings and filing certificate, 154 pages.

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 991 days.

(Continued)

(21) Appl. No.: **10/016,272**

Primary Examiner—Dang Ton

Assistant Examiner—Phuc Tran

(22) Filed: **Nov. 2, 2001**

(74) *Attorney, Agent, or Firm*—Christensen O'Connor Johnson Kindness PLLC

(65) **Prior Publication Data**

US 2002/0187770 A1 Dec. 12, 2002

(57) **ABSTRACT**

Related U.S. Application Data

(60) Provisional application No. 60/245,189, filed on Nov. 3, 2000.

A method of designing a telecommunications network, the method comprising the steps of A) for all working demand flows required to be routed in the telecommunications network, finding an initial topology of spans between nodes in the telecommunications network that is sufficient for routing all working demand flows, while attempting to minimize the cost of providing the spans; B) given the initial topology of spans identified in step A, finding a set of additional spans that ensures restorability of working demand flows that are required to be restored in case of failure of any span in the initial topology of spans, while attempting to minimize the cost of providing additional spans; and C) starting with the initial topology of spans and the additional spans identified in step B, finding a final topology of spans between nodes in the telecommunications network that attempts to minimize the total cost of the final topology of spans, while routing all working demand flows and ensuring restorability of working demand flows required to be restored in case of failure of any span in the final topology of spans. A network so designed may be implemented in whole or in part.

(51) **Int. Cl.**

H04L 12/28 (2006.01)

(52) **U.S. Cl.** **370/238; 370/256**

(58) **Field of Classification Search** 370/241,
370/248, 254, 255, 256, 257, 258, 404, 216–228,
370/235–240

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

| | | | | |
|-----------|------|---------|--------------------------|---------|
| 5,850,505 | A * | 12/1998 | Grover et al. | 714/4 |
| 6,052,796 | A | 4/2000 | Croslin | 714/4 |
| 6,154,296 | A | 11/2000 | Elahmadi et al. | 259/119 |
| 6,377,543 | B1 | 4/2002 | Grover et al. | 370/227 |
| 6,404,734 | B1 | 6/2002 | Stamatelakis et al. | 370/227 |
| 6,421,349 | B1 | 7/2002 | Grover | 370/408 |
| 6,510,139 | B1 * | 1/2003 | Yoshida | 370/238 |
| 6,819,662 | B1 * | 11/2004 | Grover et al. | 370/351 |
| 6,937,576 | B1 * | 8/2005 | Di Benedetto et al. | 370/256 |

30 Claims, 7 Drawing Sheets

